

MPO Connector MT Ferrule

Low Loss MT Ferrule by ACON

○ MPO Connector
Round 3mm



○ MPO Connector
Short Boot



○ MPO Connector
Bare Ribbon



○ MPO Connector
Ribbon Boot




Features

1. Meet IEC 61755-3-31 Grade B Standard
2. Low insertion loss, 0.35dB Max
3. Trapezoid spring enhances mechanical performance
4. Available to support 40G/100G/200G
5. Various boots are available for MPO connectors

Applications

1. Data Center application
2. Multi-channels high speed connectivity
3. WDM networks
4. Tele communication



Low Loss MT Ferrule

ACON OPTICS' MT ferrule low insertion loss of 0.35db meets the IEC 61755-3-31 Grade B standard, making this the best quality and value for your common MT ferrule needs.

ACON OPTICS COMMUNICATIONS INC.

TAIWAN-HEADQUARTER

5F., No.4, Aly. 9, Ln. 45, Baoxing Rd., Xindian Dist., New Taipei City 231, Taiwan
Tel:+886-2-2917-7668
contactus@aconoptics.com

CHINA-TIANJIN

No.32, Taixiang Road, TEDA, Tianjin, China.
Tel:+86-22-6633-2010
contactus@aconoptics.com

CHINA-SHENZHEN

No. 2, Lanjing Middle Road, Pingshan District, Shenzhen City, Guangdong, China
Tel:+86-755-3382-8888
contactus@aconoptics.com

AMERICA

Advanced-Connectek U.S.A. Inc.

3002 Dow Ave, Suite 506, Tustin, California 92780, U.S.A.
Tel: +1-714-573-1920
info@acon-us.com

www.aconoptics.com