

SC Pulling Eye Connector



Install inside microducts
6.5 mm I.D.

Maximum tensile strength **100N**

A simple and flexible solution for FTTx deployment. It is easy to deploy.

Features

- Meet the Telcordia GR-326
- Complies with IEC60874-14-2
- Maximum tensile strength at 100N
- Guaranteed insertion loss & return loss with certification
- Install inside microducts as small as 6.5 mm I.D.
- Low friction mechanism design
- Tool-less installation
- Pre-terminated pulling eye connectors

Applications

- FTTX indoor/outdoor cable
- Telecoms
- DAS

Installation

- 1 Pulling eye**
Remove the pulling eye.
- 2 Housing**
Insert the housing.
- 3 Coupling**
Slide the coupling over the housing until it snaps into place.
- 4**
Assembly **completed**.

ACON OPTICS COMMUNICATIONS INC.

TAIWAN-HEADQUARTER
5F., No.4, Aly. 9, Ln. 45, Baoxing Rd., Xindian Dist., New Taipei City 231, Taiwan
Tel: +886-2-2917-7668
contactus@aconoptics.com

CHINA-TIANJIN
No.32, Taixiang Road, TEDA, Tianjin, China.
Tel: +86-22-6633-2010
contactus@aconoptics.com

CHINA-SHENZHEN
No. 2, Lanjing Middle Road, Pingshan District, Shenzhen City, Guangdong, China
Tel: +86-755-3382-8888
contactus@aconoptics.com

AMERICA
Advanced-Connectek U.S.A. Inc.
3002 Dow Ave, Suite 506, Tustin, California 92780, U.S.A.
Tel: +1-714-573-1920
info@acon-us.com

www.aconoptics.com